

TRVVP-CY200-PUR

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
2 x 0,5	8,3	30,0	90,0	20
3 G 0,5	8,6	38,0	105,0	20
4 G 0,5	9,1	50,0	124,0	20
5 G 0,5	9,8	65,0	132,0	20
7 G 0,5	11,3	70,0	175,0	20
12 G 0,5	12,9	100,0	250,0	20
18 G 0,5	14,8	157,0	325,0	20
20 G 0,5	15,6	167,0	350,0	20
25 G 0,5	17,6	240,0	450,0	20
30 G 0,5	18,3	273,0	510,0	20
36 G 0,5	19,5	306,0	580,0	20
2 x 0,75	9,1	39,0	110,0	19
3 G 0,75	9,7	49,0	120,0	19
4 G 0,75	10,2	60,0	148,0	19
5 G 0,75	11,1	70,0	160,0	19
7 G 0,75	12,6	95,0	205,0	19
12 G 0,75	15,0	140,0	308,0	19
18 G 0,75	17,4	220,0	420,0	19
20 G 0,75	18,1	249,0	450,0	19
25 G 0,75	20,8	313,0	579,0	19
30 G 0,75	21,0	470,0	630,0	19
36 G 0,75	22,7	500,0	745,0	19
2 x 1	9,9	50,0	120,0	18
3 G 1	10,3	60,0	135,0	18
4 G 1	11,1	73,0	173,0	18
5 G 1	11,8	81,0	187,0	18
7 G 1	13,7	114,0	240,0	18
12 G 1	16,2	186,0	360,0	18
18 G 1	18,8	254,0	498,0	18
20 G 1	19,8	322,0	568,0	18

TRVVP-CY200-PUR

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
25 G 1	22,5	377,0	670,0	18
30 G 1	22,9	429,0	774,0	18
36 G 1	24,7	516,0	895,0	18
41 G 1	26,6	610,0	1032,0	18
50 G 1	28,8	690,0	1160,0	18
65 G 1	32,5	852,0	1660,0	18
2 x 1,5	10,3	64,0	145,0	16
3 G 1,5	11,2	84,0	168,0	16
4 G 1,5	11,9	99,0	217,0	16
5 G 1,5	12,8	129,0	235,0	16
7 G 1,5	14,9	148,0	325,0	16
12 G 1,5	17,9	279,0	481,0	16
18 G 1,5	20,6	393,0	675,0	16
25 G 1,5	24,8	584,0	927,0	16
30 G 1,5	25,3	607,0	1025,0	16
36 G 1,5	27,3	702,0	1210,0	16
42 G 1,5	29,4	829,0	1441,0	16
50 G 1,5	32,0	1025,0	1709,0	16
61 G 1,5	35,0	1190,0	2025,0	16
2 x 2,5	11,9	104,0	198,0	14
3 G 2,5	12,7	140,0	284,0	14
4 G 2,5	13,5	164,0	378,0	14
5 G 2,5	14,7	190,0	423,0	14
7 G 2,5	17,7	236,0	486,0	14
12 G 2,5	21,2	390,0	756,0	14
18 G 2,5	24,6	607,0	1127,0	14
20 G 2,5	26,0	661,0	1210,0	14
25 G 2,5	29,8	796,0	1530,0	14
4 G 4	16,7	222,0	448,0	12
5 G 4	18,5	328,0	533,0	12

TRVVP-CY200-PUR

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
7 G 4	21,8	360,0	678,0	12
4 G 6	18,7	305,0	636,0	10
5 G 6	20,4	441,0	772,0	10
7 G 6	24,3	505,0	1028,0	10
4 G 10	23,0	485,0	1052,0	8
5 G 10	25,2	610,0	1096,0	8
7 G 10	30,2	820,0	1530,0	8
4 G 16	26,5	840,0	1386,0	6
5 G 16	29,1	1050,0	1759,0	6
7 G 16	34,9	1510,0	2087,0	6